

## Enphase AC Battery

The **Enphase AC Battery™** is **simple** to install, very **safe** and **reliable**, and provides the lowest lifetime energy cost for both new solar customers and retrofit customers. Modular and expandable, the AC Battery lets you size the system to meet the needs of every homeowner.



### Simple

- Quick and easy single person installation
- Easily interconnects with standard household AC wiring

### Safe

- No high voltage DC in system
- Lithium iron phosphate (LFP) chemistry
- Battery safety-tested and certified by TÜV Rheinland

### Reliable

- Lithium iron phosphate (LFP) chemistry for long cycle life
- 10-year warranty
- No single point of failure

### Modular

- No need to oversize the storage system
- Easily expandable
- Low cost of entry

## Enphase AC Battery

<b>MODEL NUMBER</b>	
IQ7-B1200-LN-I-INT01-RV0 (with integrated Enphase Microinverter)	
<b>ACCESSORIES</b> (Order Separately)	<b>DIMENSIONS</b>
Enphase Wall Mount Bracket (BWM-450MM-A)	487 mm (W) x 311 mm (H) allowing 450mm battery-battery spacing
Enphase Wall Mount Bracket (BWM-600MM-A)	647 mm (W) x 311 mm (H) allowing 600mm battery-battery spacing
<b>OUTPUT DATA (AC)</b>	<b>@ 230 VAC</b>
Peak output power	270 VA
Rated (continuous) output power	260 VA
Nominal frequency	50 Hz
Extended line to neutral voltage range	184 to 276 VAC
Extended frequency range	45 to 55 Hz
Power factor	0.7 leading to 0.7 lagging
Maximum units per 20 A branch circuit	13
Peak inverter efficiency	96.9%
<b>BATTERY CHEMISTRY</b>	
Capacity	1.2 kWh
Depth of discharge (usable capacity)	100%
Ambient operating temperature range	-20°C to 45°C
Chemistry	Lithium Iron Phosphate (LFP)
Battery safety certifications	TUV Rheinland
Roundtrip cell efficiency <sup>1</sup>	96%
<b>MECHANICAL DATA</b>	
Dimensions	390 mm (W) x 325 mm (H) x 220 mm (D) (without bracket)
Weight	23 kg
Installation	Wall mounted in an indoor space using standard AC wiring in conduit or in wall, where allowed.
Enclosure	Indoor – IP20
Cooling	Natural convection – No active or passive cooling infrastructure required
Grid configuration	TN-C-S
<b>FEATURES AND COMPLIANCE</b>	
Compatibility	Compatible with grid-tied PV systems using the Enphase Envoy-S Metered™ gateway
Communication	Power Line Communication (PLC), TCP/IP through Envoy-S <sup>2</sup>
Services	Maximising self-consumption of solar, time-of-use bill management, power export limiting <sup>3</sup>
Monitoring	Enlighten Manager and MyEnlighten monitoring options
Safety of cells and battery pack	TUV Rheinland (IEC 62619)
Compliance	AS/NZS 4777.2:2015 AS/NZS CISPR 22, AS/NZS 62040.1.1, UN 38.3, Australia Battery Assurance Program
<b>LIMITED WARRANTY</b>	
Limited Warranty <sup>4</sup>	80% capacity , up to 10 years or 3650 cycles

1. At 30°C.

2. Software Version 4.10 or later.

3. Optional. Requires Enphase S/IQ-Series Microinverters™ to implement.

4. Whichever occurs first. Restrictions apply. Average Annual internal temperature below 23° C

To learn more about Enphase offerings, visit [enphase.com/au](https://enphase.com/au)

© 2019 Enphase Energy. All rights reserved. All trademarks or brands used are the property of Enphase Energy, Inc.

